



## Texas Granite Homogeneous Commercial Tile SPECIFICATIONS

Gauge	3.17 mm (0.125")	
Sizes	<b>Texas Granite</b> <ul style="list-style-type: none"> <li>▪ 12" x 12" (305 mm x 305 mm) Micro-Ground</li> <li>▪ 24" x 24" (610 mm x 610 mm) Micro-Ground</li> <li>▪ 36" x 36" (915 mm x 915 mm)</li> </ul> <b>Solid Colors:</b> <ul style="list-style-type: none"> <li>▪ 12" x 12" (305 mm x 305 mm) Micro-Ground</li> <li>▪ 36" x 36" (915 mm x 915 mm)</li> </ul>	
Colors	Texas Granite	31
	Solid Colors	4
Construction	Homogenous TPe	
ASTM F 1700	Class 1, Type A	
<ul style="list-style-type: none"> <li>▪ Dimensional Stability</li> <li>▪ Squareness</li> </ul>		
Fire Resistance	Class 1	
<ul style="list-style-type: none"> <li>▪ ASTM E-84 (Steiner Tunnel)</li> <li>▪ CAN4-S102.2 M80</li> </ul>	Class 1	
FLAMMABILITY	Class 1	
<ul style="list-style-type: none"> <li>▪ ASTM E-662 (Flame Spread Index)</li> <li>▪ CAN4-S102.2. M80</li> </ul>	Class 1	
ASTM E-648 (NFPA 253) – Critical Radiant Flux	Class 1 >1.0 W/sq. cm	
ASTM D-1894 – Slip Resistance	Meets ADA Guidelines	
ASTM D-3389 – Abrasion Resistance	0.8g	
ASTM F-970 (modified) – Static Load	2500 psi	
Flexibility	Excellent	
ASTM 2240 - Hardness	45 ± 5 Shore D	
ASTM F-925 – Chemical Resistance	Resists oils, fats, alkalis, diluted acids, gasoline, blood, juice, etc. (Details available upon request)	
Limited Wear Warranty	10 Years	
Maintenance	No Wax	

Estrie Products International, a Division of American Biltrite  
 Telephone: 1-800-479-0190  
 Fax: 1-800-810-5731  
 E-Mail: [flooring@american-biltrite.com](mailto:flooring@american-biltrite.com)



July 25, 2007 Version 1  
 Page 1 of 1